

R35 Coil Bracket for Toyota JZ

- Includes mounting hardware and PCV block off



Instructions

- 1.) Disconnect the battery negative cable from the battery to avoid any chances of an electrical short.
- 2.) Remove the ignition coil cover, existing ignition coils, ignition leads and ignition harness. Depending on the engine, the valve cover balance breather ports may need to be removed, blocked off with the supplied plugs, and only the outer ports used for coil clearance.
- 3.) Install the R35 ignition coil bracket and ignition coils onto the cylinder head using the included mounting hardware.
- 4.) Before powering up the R35 ignition coils, ensure that the Haltech ECU is set to use direct fire, falling edge, constant charge dwell mode, and the recommended R35 ignition coil dwell times for the ignition system settings. Failure to do so will damage the ignition coils resulting to no spark or low spark energy.
- 5.) Plug the Haltech ignition coil harness, reconnect the battery, and proceed to start the engine.

HT-120100

Revision #1

Need more help?



AUS: +61 2 9729 0999
Europe: +43 720 883 968

USA: (888) 298 8116
UK: +44 121 285 6650

NZ: +64 988 706 16



www.haltech.com/support



support@haltech.com

HT-120100
R35 Coil Bracket for
Toyota JZ
(inc mounting hardware)



In many states it is unlawful to tamper with your vehicle's emissions equipment.

Haltech Off-Road Usage Policy

Haltech products are designed and sold for sanctioned off-road/competition, non-registered or non-emissions controlled vehicles only and may never be used on a public road or highway. Using Haltech products for street/road use on public roads or highways is prohibited by law unless a specific regulatory exemption exists (more information can be found on the EMA Action Network website www.semason.com/emissions for state details in the USA).

It is the responsibility of the installer and/or user of this product to ensure compliance with all applicable local and federal laws and regulations. Please check with your local vehicle authority before purchasing, using or installing any Haltech product.

No responsibility whatsoever is accepted by Haltech for the fitment of Haltech Products. The user is clearly on the installer to ensure that both their knowledge and the parts selected are correct for that particular application. Any damage to parts or consequential damage or costs resulting from the incorrect installation of Haltech products are totally the responsibility of the installer.

Unless specified otherwise, Haltech warrants its products to be free from defects in material or workmanship for a period of 12 months from the date of purchase. Proof of purchase in the form of a copy of the original purchase invoice, receipt or bill of sale which indicates that the product is within the warranty period, must be presented to obtain warranty service. If the Haltech product is found to be defective as mentioned above, it will be replaced or repaired if returned prepaid along with proof of purchase. This shall constitute the sole liability of Haltech. To the extent permitted by law, the foregoing is exclusive and in lieu of all other warranties or representations, either expressed or implied, including any implied warranty of merchantability or fitness. In no event shall Haltech, be liable for special or consequential damages.

Product Returns

Please include a copy of the original purchase invoice, receipt or bill of sale along with the unused, undamaged product and its original packaging. Any product returned with missing accessory items or packaging will incur extra charges to return the item to a re-salable condition. All product returns must be sent via a freight method with adequate tracking, insurance and proof of delivery services. Haltech will not be held responsible for product returns lost during transit. The sale of any sensor or accessory that is supplied in sealed packaging is strictly non-refundable if the sealed packaging has been opened or tampered with. This will be clearly noted on the product packaging. If you do not accept these terms please return the sensor in its original unopened packaging within 30 days for a full refund.

Returning a sensor or accessory product within 30 days of purchase: Product may be returned for credit or full refund. (Any sealed packaging must not have been opened or tampered with)

Returning a sensor or accessory product after 30 days of purchase: Product may be returned for credit only (no refunds given) and is subject to a 10% Restocking fee. (Any sealed packaging must not have been opened or tampered with)

Version 6.0