In many states it is unlawful to tamper with your vehicle's emissions equipment. Haltech Off-Road Usage Policy

(ASU and in state by state by state details in the USU). specific regulatory exemption exists (more information can be found on the SEMA Action Network Using Haltech products for street/road use on public roads or highways is prohibited by law unless a non-emissions controlled vehicles only and may never be used on a public road or highway. Haltech products are designed and sold for sanctioned off-road/competition, non-registered or

before purchasing, using or installing any Haltech product. applicable local and federal laws and regulations. Please check with your local vehicle authority It is the responsibility of the installer and/or user of this product to ensure compliance with all

that particular application. Any damage to parts or consequential damage or costs resulting from the is clearly on the installer to ensure that both their knowledge and the parts selected are correct for No responsibility whatsoever is accepted by Haltech for the fitment of Haltech Products. The onus Installation of Haltech Products

Haltech Limited Warranty

incorrect installation of Haltech products are totally the responsibility of the installer.

liable for special or consequential damages. implied, including any implied warranty of merchantability or fitness. In no event shall Haltech, be foregoing is exclusive and in lieu of all other warranties or representations, either expressed or of purchase. This shall constitute the sole liability of Haltech. To the extent permitted by law, the be defective as mentioned above, it will be replaced or repaired if returned prepaid along with proof the warranty period, must be presented to obtain warranty service. If the Haltech product is found to coby of the original purchase invoice, receipt or bill of sale which indicates that the product is within workmanship for a period of 12 months from the date of purchase. Proof of purchase in the form of a Unless specified otherwise, Haltech warrants its products to be free from defects in material or

Product Returns

nıl retund. accept these terms please return the sensor in its original unopened packaging within 30 days for a been opened or tampered with. This will be clearly noted on the product packaging. If you do not accessory that is supplied in sealed packaging is strictly non-refundable if the sealed packaging has Haltech will not be held responsible for product returns lost during transit. The sale of any sensor or must be sent via a freight method with adequate tracking, insurance and proof of delivery services. packaging will incur extra charges to return the item to a re-saleable condition. All product returns undamaged product and its original packaging. Any product returned with missing accessory items or Please include a copy of the original purchase invoice, receipt or bill of sale along with the unused,

for credit or full refund. (Any sealed packaging must not have been opened or tampered with) Returning a sensor or accessory product within 30 days of purchase: Product may be returned

(una pave been opened or tampered with) tor creationly (no returds given) and is subject to a 10% Restocking ree. (Any seared packaging Returning a sensor or accessory product after 30 days of purchase: Product may be returned

Need more help? HT-186506 AUS: +61 2 9729 0999 USA: (888) 298 8116 NZ: +64 988 706 16 Europe: +43 720 883 968 UK: +44 121 285 6650 support@haltech.com www.haltech.com/support Revision #1

Pin Function Rebel LS connection Motor Drive 1 IAC 1 (HBO) А R Ground Sensor ground С Motor Drive 2 IAC 2 (HBO) D Ground Sensor ground +5V F +5V F TPS 1 Throttle TPS 1 TPS 2 Throttle TPS 2 G Н +5V +5V



8 pin LS DBW throttle HT-186506 8 pin DBW adapter Throttle connector HT-186500 - Nexus Rebel LS main terminated harness

A Ă



1910 Adapter values of the second sec

Vexus Rebel LS

902981-TH



Nexus Rebel LS - 8 pin DBW Adapter Harness

This adapter is used to connect the throttle connector on the Nexus Rebel LS main terminated harness to an 8 pin LS DBW throttle.